



WEM BEARING SIZE CONFIGURATION

SQUIRREL CAGE ELECTRIC MOTORS 380 / 415 & 525V, THREE PHASE

FULL LOAD OUTPUT		CAST IRON FRAME		BEARING SIZE	GREASE INTERVAL		BEARING SIZE	GREASE INTERVAL	
kW	Rpm	Frame	Shaft (mm)	DRIVE END	GRAMS	HOURS	NON-DRIVE END	GRAMS	HOURS
0.18	2720	63	11	6201ZZ	N/A	N/A	6201ZZ	N/A	N/A
	1310	63	11	6201ZZ	N/A	N/A	6201ZZ	N/A	N/A
0.25	2720	63	11	6201ZZ	N/A	N/A	6201ZZ	N/A	N/A
	1330	71	14	6202ZZ	N/A	N/A	6202ZZ	N/A	N/A
0.37	850	80	19	6204ZZ	N/A	N/A	6204ZZ	N/A	N/A
	2740	71	14	6202ZZ	N/A	N/A	6202ZZ	N/A	N/A
	1330	71	14	6202ZZ	N/A	N/A	6202ZZ	N/A	N/A
	890	80	19	6204ZZ	N/A	N/A	6204ZZ	N/A	N/A
0.55	660	90S	24	6205ZZ	N/A	N/A	6205ZZ	N/A	N/A
	2740	71	14	6202ZZ	N/A	N/A	6202ZZ	N/A	N/A
	1390	80	19	6204ZZ	N/A	N/A	6204ZZ	N/A	N/A
	890	80	19	6204ZZ	N/A	N/A	6204ZZ	N/A	N/A
0.75	660	90L	24	6205ZZ	N/A	N/A	6205ZZ	N/A	N/A
	2830	80	19	6204ZZ	N/A	N/A	6204ZZ	N/A	N/A
	1390	80	19	6204ZZ	N/A	N/A	6204ZZ	N/A	N/A
	910	90S	24	6205ZZ	N/A	N/A	6205ZZ	N/A	N/A
1.1	690	100L	28	6206ZZ	N/A	N/A	6206ZZ	N/A	N/A
	2830	80	19	6204ZZ	N/A	N/A	6204ZZ	N/A	N/A
	1400	90S	24	6205ZZ	N/A	N/A	6205ZZ	N/A	N/A
	910	90L	24	6205ZZ	N/A	N/A	6205ZZ	N/A	N/A
1.5	690	100L	28	6206ZZ	N/A	N/A	6206ZZ	N/A	N/A
	2840	90S	24	6205ZZ	N/A	N/A	6205ZZ	N/A	N/A
	1400	90L	24	6205ZZ	N/A	N/A	6205ZZ	N/A	N/A
	940	100L	28	6206ZZ	N/A	N/A	6206ZZ	N/A	N/A
2.2	680	112M	28	6306ZZ	N/A	N/A	6306ZZ	N/A	N/A
	2840	90L	24	6205ZZ	N/A	N/A	6205ZZ	N/A	N/A
	1430	100L	28	6206ZZ	N/A	N/A	6206ZZ	N/A	N/A
	940	112M	28	6306ZZ	N/A	N/A	6306ZZ	N/A	N/A
3	710	132S	38	6308ZZ	N/A	N/A	6308ZZ	N/A	N/A
	2870	100L	28	6206ZZ	N/A	N/A	6206ZZ	N/A	N/A
	1430	100L	28	6206ZZ	N/A	N/A	6206ZZ	N/A	N/A
	960	132S	38	6308ZZ	N/A	N/A	6308ZZ	N/A	N/A
4	710	132M	38	6308ZZ	N/A	N/A	6308ZZ	N/A	N/A
	2890	112M	28	6306ZZ	N/A	N/A	6306ZZ	N/A	N/A
	1440	112M	28	6306ZZ	N/A	N/A	6306ZZ	N/A	N/A
	960	132M	38	6308ZZ	N/A	N/A	6308ZZ	N/A	N/A
5.5	720	160M	42	6209 C3	30	3000	6209 C3	30	3000
	2900	132S	38	6308ZZ	N/A	N/A	6308ZZ	N/A	N/A
	1440	132S	38	6308ZZ	N/A	N/A	6308ZZ	N/A	N/A
	960	132M	38	6308ZZ	N/A	N/A	6308ZZ	N/A	N/A
7.5	720	160M	42	6209 C3	30	3000	6209 C3	30	3000
	2900	132S	38	6308ZZ	N/A	N/A	6308ZZ	N/A	N/A
	1440	132M	38	6308ZZ	N/A	N/A	6308ZZ	N/A	N/A
	970	160M	42	6209 C3	30	3000	6209 C3	30	3000
	720	160L	42	6209 C3	30	3000	6209 C3	30	3000



WEM BEARING SIZE CONFIGURATION

SQUIRREL CAGE ELECTRIC MOTORS 380 / 415 & 525V, THREE PHASE

FULL LOAD OUTPUT		CAST IRON FRAME		BEARING SIZE	GREASE INTERVAL		BEARING SIZE	GREASE INTERVAL	
kW	Rpm	Frame	Shaft (mm)	DRIVE END	GRAMS	HOURS	NON-DRIVE END	GRAMS	HOURS
9.2	2930	132M	38	6308ZZ	N/A	N/A	6308ZZ	N/A	N/A
	1460	132M	38	6308ZZ	N/A	N/A	6308ZZ	N/A	N/A
11	2930	160M	42	6209 C3	30	3000	6209 C3	30	3000
	1460	160M	42	6209 C3	30	3000	6209 C3	30	3000
	970	160L	42	6209 C3	30	3000	6209 C3	30	3000
	730	180L	48	6211 C3	30	3000	6211 C3	30	3000
15	2930	160M	42	6209 C3	30	3000	6209 C3	30	3000
	1460	160L	42	6209 C3	30	3000	6209 C3	30	3000
	970	180L	48	6211 C3	30	3000	6211 C3	30	3000
	730	200L	55	6312 C3	60	3000	6312 C3	60	3000
18.5	2930	160L	42	6209 C3	30	2000	6209 C3	30	2000
	1470	180M	48	6211 C3	30	3000	6211 C3	30	3000
	970	200L	55	6312 C3	60	3000	6312 C3	60	3000
	730	225M	60	NU313 C3	80	3000	6313 C3	80	3000
22	2940	180M	48	6211 C3	30	2000	6211 C3	30	2000
	1470	180L	48	6211 C3	30	3000	6211 C3	30	3000
	970	200L	55	6312 C3	60	3000	6312 C3	60	3000
	740	225S/M	60	NU313 C3	80	3000	6313 C3	80	3000
30	2950	200L	55	6312 C3	60	2000	6312 C3	60	2000
	1470	200L	55	6312 C3	60	3000	6312 C3	60	3000
	980	225S/M	60	NU313 C3	80	3000	6313 C3	80	3000
	740	250S/M	70	NU315 C3	100	3000	6315 C3	100	3000
37	2950	200L	55	6312 C3	60	2000	6312 C3	60	2000
	1480	225S/M	60	NU313 C3	80	2000	6313 C3	80	2000
	980	250S/M	70	NU315 C3	100	3000	6315 C3	100	3000
	740	250S/M	70	NU315 C3	100	3000	6315 C3	100	3000
45	2970	225S/M	55	NU313 C3	80	2000	6312 C3	80	2000
	1480	225S/M	60	NU313 C3	80	2000	6313 C3	80	2000
	980	250S/M	70	NU315 C3	100	3000	6315 C3	100	3000
	740	280S/M	80	NU317 C3	120	3000	6314 C3	120	3000
55	2970	250S/M	60	NU315 C3	100	2000	6315 C3	100	2000
	1480	250S/M	70	NU315 C3	100	2000	6315 C3	100	2000
	980	280S/M	80	NU317 C3	120	3000	6314 C3	120	3000
	740	280S/M	80	NU317 C3	120	3000	6314 C3	120	3000
75	2970	250S/M	60	NU315 C3	100	2000	6315 C3	100	2000
	1480	250S/M	70	NU315 C3	100	2000	6315 C3	100	2000
	990	280S/M	80	NU317 C3	120	3000	6315 C3	120	3000
	740	315S/M	85	NU319 C3	120	3000	6319 C3	120	3000
90	2970	280S/M	65	NU314 C3	80	2000	6314 C3	80	2000
	1490	280S/M	80	NU317 C3	120	1500	6314 C3	120	2000
	990	315S/M	85	NU319 C3	120	3000	6319 C3	120	3000
	740	315S/M	85	NU319 C3	120	3000	6319 C3	120	3000



WEM BEARING SIZE CONFIGURATION

SQUIRREL CAGE ELECTRIC MOTORS 380 / 415 & 525V, THREE PHASE

FULL LOAD OUTPUT		CAST IRON FRAME		BEARING SIZE	GREASE INTERVAL		BEARING SIZE	GREASE INTERVAL	
kW	Rpm	Frame	Shaft (mm)	DRIVE END	GRAMS	HOURS	NON-DRIVE END	GRAMS	HOURS
110	2980	280S/M	65	NU314 C3	80	2000	6314 C3	80	2000
	1490	280S/M	80	NU317 C3	120	1500	6314 C3	120	1500
	990	315S/M	85	NU319 C3	120	3000	6319 C3	120	3000
	740	315S/M	85	NU319 C3	120	3000	6319 C3	120	3000
132	2980	315S/M	65	NU317 C3	120	1500	6317 C3	120	1500
	1490	315S/M	85	NU319 C3	120	1500	6319 C3	120	1500
	990	315M/L	85	NU319 C3	120	3000	6319 C3	120	3000
	740	355M/L	100	NU322 C3	220	3000	6322 C3	220	3000
160	2980	315M/L	65	NU317 C3	120	1500	6317 C3	120	1500
	1490	315M/L	85	NU319 C3	120	1500	6319 C3	120	1500
	990	355M/L	100	NU322 C3	220	2000	6322 C3	220	2000
	740	355M/L	100	NU322 C3	220	3000	6322 C3	220	3000
185	2980	315M/L	70	NU317 C3	120	1500	6317 C3	120	1500
	1490	315M/L	90	NU319 C3	120	1500	6319 C3	120	1500
	990	355M/L	100	NU322 C3	220	2000	6322 C3	220	2000
	740	355M/L	100	NU322 C3	220	3000	6322 C3	220	3000
200	2980	315M/L	70	NU317 C3	120	1500	6317 C3	120	1500
	1490	315M/L	90	NU319 C3	120	1500	6319 C3	120	1500
	990	355M/L	100	NU322 C3	220	2000	6322 C3	220	2000
	740	355M/L	100	NU322 C3	220	3000	6322 C3	220	3000
220	2980	355M/L	90	NU319 C3	120	1500	6319 C3	120	1500
	1485	315M/L	90	NU319 C3	120	1500	6319 C3	120	1500
	1485	355M/L	100	NU322 C3	220	1000	6322 C3	220	1000
	990	355M/L	100	NU322 C3	220	2000	6322 C3	220	2000
	740	355M/L	100	NU322 C3	220	3000	6322 C3	220	3000
250	2980	355M/L	90	NU319 C3	120	1500	6319 C3	120	1500
	1485	315M/L	90	NU319 C3	120	1500	6319 C3	120	1500
	1485	355M/L	90	NU322 C3	220	1000	6322 C3	220	1000
	990	355M/L	100	NU322 C3	220	2000	6322 C3	220	2000
275	2980	355M/L	90	NU319 C3	120	1500	6319 C3	120	1500
	1485	355M/L	100	NU322 C3	220	1000	6322 C3	220	1000
	980	355M/L	100	NU322 C3	220	2000	6322 C3	220	2000
315	2980	355M/L	90	NU319 C3	120	1500	6319 C3	120	1500
	1485	355M/L	100	NU322 C3	220	1000	6322 C3	220	1000
330	4P	355M/L	100	NU322 C3	220	1000	6322 C3	220	1000
350	4P	355M/L	100	NU322 C3	220	1000	6322 C3	220	1000
375	4P	355M/L	100	NU322 C3	220	1000	6322 C3	220	1000
400	4P	355M/L	100	NU322 C3	220	1000	6322 C3	220	1000
450	4P	400M/L	110	NU326 C3	300	1000	6326 C3	300	1000
500	4P	400M/L	110	NU326 C3	300	1000	6326 C3	300	1000
560	4P	400M/L	110	NU326 C3	300	1000	6326 C3	300	1000
630	4P	400M/L	110	NU326 C3	300	1000	6326 C3	300	1000